



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 34.29x5.33 - EDPM - Zolfo - 70 Shore A - Nero - ORS11204

<https://www.o-ring-stocks.eu/it/o-ring-34.29x5.33-edpm-zolfo-70-shore-a-nero-ors11204>

### Specificaties

|               |                           |
|---------------|---------------------------|
| Productnummer | 11204                     |
| EAN           | 6150549975933             |
| Merk          | Eurolast                  |
| Categorie     | EPDM O-Rings - 70 Shore A |
| Materiaal     | EPDM                      |
| Kleur         | Zwart                     |
| Kleur         | Black                     |

### Basis Specificaties

|                    |                                                          |
|--------------------|----------------------------------------------------------|
| Keurmerk           | None                                                     |
| Chemische Benaming | Ethylene propylene diene monomer                         |
| Extra omschrijving | O-ring 34.29x5.33 EPDM                                   |
| Maat in tekst      | thirty four comma twenty nine by five comma thirty three |
| Materiaal          | EPDM                                                     |
| Merknamen          | Dow Chemical - ExxonMobil - and Lion Elastomers          |
| Omschrijving-2     | O-ring EPDM 34.29x5.33                                   |
| Verpakkingseenheid | O-ring                                                   |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 324       |
| DIN 3771 Maat | 34.29x5.33   |
| SMS 1586 Maat | 34.29 X 5.33 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.33 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 34.29 mm   |
| Temperatuur Max     | 125 °C     |
| Temperatuur Min     | -40 °C     |
| Vulkanisatie        | Sulfur     |