



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 50.16x5.33 - VMQ - MVQ - Silicone - 70 Shore A - Transparant -

<https://www.o-ring-stocks.eu/nl/o-ring-50.16x5.33-vmq-mvq-silicone-70-shore-a-transparant-ors49530>

### Specificaties

|               |                                        |
|---------------|----------------------------------------|
| Productnummer | 49530                                  |
| EAN           | 6150548584556                          |
| Merk          | Eurolast                               |
| Categorie     | VMQ O-Rings - 70 Shore A - Transparant |
| Materiaal     | VMQ - MVQ - Silicone                   |
| Kleur         | Transparant                            |
| Kleur         | Transparant                            |

### Basis Specificaties

|                       |                                                |
|-----------------------|------------------------------------------------|
| Keurmerk              | FDA 21 CFR 177.2600 – EC1935/2004              |
| Alternatieve benaming | Silicone Rubber - PVMQ                         |
| Chemische Benaming    | Vinyl Methyl Silicone                          |
| Extra omschrijving    | O-ring 50.16x5.33 VMQ - Silicone               |
| Maat in tekst         | fifty comma sixteen by five comma thirty three |
| Materiaal             | Silicone - VMQ - MVQ                           |
| Merkenamen            | Eriks - Wacker - Eastern Seals - and BlueStar  |
| Omschrijving-2        | O-ring VMQ - MVQ - Silicone 50.16x5.33         |
| Verpakkingseenheid    | O-ring                                         |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 329       |
| DIN 3771 Maat | 50.16x5.33   |
| SMS 1586 Maat | 50.16 X 5.33 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.33 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 50.16 mm   |
| Temperatuur Max     | 210 °C     |
| Temperatuur Min     | -50 °C     |