



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 209.14x3.53 - FKM - FPM - Viton - 80 Shore A - Zwart - ORS34964

<https://www.o-ring-stocks.eu/nl/o-ring-209.14x3.53-fkm-fpm-viton-80-shore-a-zwart-ors34964>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 34964                            |
| EAN           | 6150548379350                    |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Zwart |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Zwart                            |
| Kleur         | Black                            |

### Basis Specificaties

|                       |                                                                |
|-----------------------|----------------------------------------------------------------|
| Keurmerk              | None                                                           |
| Alternatieve benaming | Viton® - FKM                                                   |
| Chemische Benaming    | Fluorocarbon Rubber                                            |
| Extra omschrijving    | O-ring 209.14x3.53 FPM - Viton                                 |
| Maat in tekst         | two hundred and nine comma fourteen by three comma fifty three |
| Materiaal             | FKM - FPM - Viton                                              |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                        |
| Omschrijving-2        | O-ring FKM - FPM - Viton 209.14x3.53                           |
| Verpakkingseenheid    | O-ring                                                         |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 267        |
| DIN 3771 Maat | 209.14x3.53   |
| SMS 1586 Maat | 209.14 X 3.53 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.53 mm    |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 209.14 mm  |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |