




O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 37.77x2.62 - FKM - FPM - Viton - 80 Shore A - Green - ORS50311

<https://www.o-ring-stocks.eu/nl/o-ring-37.77x2.62-fkm-fpm-viton-80-shore-a-green-ors50311>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 50311                            |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Groen |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Groen                            |
| Kleur         | Green                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                            |
| Chemische Benaming    | Fluorocarbon Rubber                                     |
| Extra omschrijving    | O-ring 37.77x2.62 FPM - Viton                           |
| Maat in tekst         | thirty seven comma seventy seven by two comma sixty two |
| Materiaal             | FKM - FPM - Viton                                       |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                 |
| Omschrijving-2        | O-ring FKM - FPM - Viton 37.77x2.62                     |
| Verpakkingseenheid    | O-ring                                                  |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 128       |
| DIN 3771 Maat | 37.77x2.62   |
| SMS 1586 Maat | 37.77 X 2.62 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 2.62 mm    |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 37.77 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |