



O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 139.38x2.62 - FKM - FPM - Viton - 80 Shore A - Bruin - ORS7043

<https://www.o-ring-stocks.eu/nl/o-ring-139.38x2.62-fkm-fpm-viton-80-shore-a-bruin-ors7043>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 7043                             |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Bruin |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Bruin                            |
| Kleur         | Brown                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                                       |
|-----------------------|-----------------------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                                          |
| Chemische Benaming    | Fluorocarbon Rubber                                                   |
| Extra omschrijving    | O-ring 139.38x2.62 FPM - Viton                                        |
| Maat in tekst         | one hundred and thirty nine comma thirty eight by two comma sixty two |
| Materiaal             | FKM - FPM - Viton                                                     |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                               |
| Omschrijving-2        | O-ring FKM - FPM - Viton 139.38x2.62                                  |
| Verpakkingseenheid    | O-ring                                                                |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 161        |
| DIN 3771 Maat | 139.38x2.62   |
| SMS 1586 Maat | 139.38 X 2.62 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 2.62 mm    |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 139.38 mm  |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |