



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 62.3x5.7 - FKM - FPM - Viton - 75 Shore A - Zwart - ORS161439

<https://www.o-ring-stocks.eu/nl/o-ring-62.3x5.7-fkm-fpm-viton-75-shore-a-zwart-ors161439>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 161439                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 75 Shore A - Zwart |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | ZWART                            |
| Kleur         | Black                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                              |
|-----------------------|----------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                 |
| Chemische Benaming    | Fluorocarbon Rubber                          |
| Extra omschrijving    | O-ring 62.3x5.7 FKM - FPM - Viton            |
| Maat in tekst         | sixty two comma thirty by five comma seventy |
| Materiaal             | FKM - FPM - Viton                            |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin      |
| Omschrijving-2        | O-ring FKM - FPM - Viton 62.3x5.7            |
| Verpakkingseenheid    | O-ring                                       |

### Alternative maat

|               |          |
|---------------|----------|
| DIN 3771 Maat | 62.3x5.7 |
| ISO 3601 Maat | 62.3x5.7 |
| SMS 1586 Maat | 62.3x5.7 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.7 mm     |
| Hardheid            | 75 Shore A |
| ID (binnendiameter) | 62.3 mm    |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |