



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 106x5.3 - NBR - Nitrile - 70 Shore A - Zwart - ORS12256

<https://www.o-ring-stocks.eu/nl/o-ring-106x5.3-nbr-nitrile-70-shore-a-zwart-ors12256>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 12256                    |
| EAN           | 6150547118189            |
| Merk          | Eurolast                 |
| Categorie     | NBR O-Rings - 70 Shore A |
| Materiaal     | Nitrile NBR-Buna         |
| Kleur         | Zwart                    |
| Kleur         | Black                    |

### Basis Specificaties

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Keurmerk              | None                                          |
| Alternatieve benaming | Nitrile Rubber - NBR                          |
| Chemische Benaming    | Acrylonitrile butadiene rubber                |
| Extra omschrijving    | O-ring 106x5.3 Nitrile NBR                    |
| Maat in tekst         | one hundred and six zero by five comma thirty |
| Materiaal             | NBR - Nitrile                                 |
| Merkenamen            | Lanxess - Zeon - and LG Chem                  |
| Omschrijving-2        | O-ring NBR - Nitrile 106x5.3                  |
| Verpakkingseenheid    | O-ring                                        |

### Alternative maat

|                  |           |
|------------------|-----------|
| DIN 3771 Maat    | 106x5.3   |
| NF T 47-501 Maat | D1060     |
| SMS 1586 Maat    | 106 X 5.3 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.3 mm     |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 106 mm     |
| Temperatuur Max     | 135 °C     |
| Temperatuur Min     | -30 °C     |