



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 94.97x1.78 - FKM - FPM - Viton - 70 Shore A - Zwart - ORS41322

<https://www.o-ring-stocks.eu/nl/o-ring-94.97x1.78-fkm-fpm-viton-70-shore-a-zwart-ors41322>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 41322                            |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 70 Shore A - Zwart |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Zwart                            |
| Kleur         | Black                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                           |
|-----------------------|-----------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                              |
| Chemische Benaming    | Fluorocarbon Rubber                                       |
| Extra omschrijving    | O-ring 94.97x1.78 FPM - Viton                             |
| Maat in tekst         | ninety four comma ninety seven by one comma seventy eight |
| Materiaal             | FKM - FPM - Viton                                         |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                   |
| Omschrijving-2        | O-ring FKM - FPM - Viton 94.97x1.78                       |
| Verpakkingseenheid    | O-ring                                                    |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 044       |
| DIN 3771 Maat | 94.97x1.78   |
| SMS 1586 Maat | 94.97 X 1.78 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 1.78 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 94.97 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |