




O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 129.54x5.33 - FKM - FPM - Viton - 90 Shore A - Green - ORS42139

<https://www.o-ring-stocks.eu/nl/o-ring-129.54x5.33-fkm-fpm-viton-90-shore-a-green-ors42139>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 42139                            |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 90 Shore A - Groen |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Groen                            |
| Kleur         | Green                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                                         |
|-----------------------|-------------------------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                                            |
| Chemische Benaming    | Fluorocarbon Rubber                                                     |
| Extra omschrijving    | O-ring 129.54x5.33 FPM - Viton                                          |
| Maat in tekst         | one hundred and twenty nine comma fifty four by five comma thirty three |
| Materiaal             | FKM - FPM - Viton                                                       |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                                 |
| Omschrijving-2        | O-ring FKM - FPM - Viton 129.54x5.33                                    |
| Verpakkingseenheid    | O-ring                                                                  |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 354        |
| DIN 3771 Maat | 129.54x5.33   |
| SMS 1586 Maat | 129.54 X 5.33 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.33 mm    |
| Hardheid            | 90 Shore A |
| ID (binnendiameter) | 129.54 mm  |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |