



O-ring-Stocks.eu - Techniparts

Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 405,26x5,33 - FFKM - FFPM - Conform FDA - High Temp - 80 Shore

<https://www.o-ring-stocks.eu/nl/o-ring-405.26x5.33-ffkm-ffpm-hoge-temp-fda-ec19352004-usp-class-vi-80-shore-a-wit-ors92416>

### Specificaties

Productnummer	92416
Merk	Eurolast
Categorie	FFKM O-Rings - 80 Shore A - F808W95 - Wit
Materiaal	FFKM - FFPM
Kleur	Wit

### Basis Specificaties

Keurmerk	Conform FDA - (300°C)
Kleur	White

Afmetingen	405.26x5.33
Equivalent	PPE Perlast G80H
Materiaal	FFKM - FFPM
Omschrijving-2	O-ring FFKM - FFPM 405.26x5.33
Type Dichting	O-ring

### Alternative maat

AS568 Maat	AS 139
DIN 3771 Maat	405.26x5.33
Maat in tekst	four hundred and five comma twenty six by five comma thirty three
SMS 1586 Maat	405.26 X 5,33

### Basis Specificaties

CS (Snoer dikte)	5.33 mm
Hardheid	80 Shore A
ID (Binnendiameter)	405.26 mm
Temperatuur Max	300 °C
Temperatuur Min	-15 °C

### Equivalent aan

Dupont Kalrez® Equivalent	Not Known
Freudenberg Simriz® Equivalent	Not Known
Greene Tweed Chemraz® Equivalent	Not Known
Parker Parafluor® Equivalent	Not Known

## Specificaties

PPE Perlast® Equivalent PPE Perlast G80H

Trelleborg Isolast® Equivalent Not Known

## Overige Specs

Alternatieve benaming FFPM – Dupont Kalrez

Chemische Benaming Perfluoroelastomer

Extra omschrijving O-ring 405.26x5.33 FFKM - FFPM

Merkmamen Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax

## Technische Specs

Compressieset 28 %

Soortelijk Gewicht 2,55 (+/- 0,03) g/cm<sup>3</sup>

Treksterkte 13,2 MPa

Ultimale Rek 100 %