



O-ring-Stocks.eu - Techniparts

Rondweg 26
8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 304,39x3,53 - FFKM - FFPM - Conform FDA - High Temp - 80 Shore

<https://www.o-ring-stocks.eu/nl/o-ring-304.39x3.53-ffkm-ffpm-hoge-temp-fda-ec19352004-usp-class-vi-80-shore-a-wit-ors92332>

Specificaties

Productnummer	92332
Merk	Eurolast
Categorie	FFKM O-Rings - 80 Shore A - F808W95 - Wit
Materiaal	FFKM - FFPM
Kleur	Wit

Basis Specificaties

Keurmerk	Conform FDA - (300°C)
Kleur	White

Afmetingen	304.39x3.53
Equivalent	PPE Perlast G80H
Materiaal	FFKM - FFPM
Omschrijving-2	O-ring FFKM - FFPM 304.39x3.53
Type Dichting	O-ring

Alternative maat

AS568 Maat	AS 006
DIN 3771 Maat	304.39x3.53
Maat in tekst	three hundred and four comma thirty nine by three comma fifty three
SMS 1586 Maat	304.39 X 3,53

Basis Specificaties

CS (Snoer dikte)	3.53 mm
Hardheid	80 Shore A
ID (Binnendiameter)	304.39 mm
Temperatuur Max	300 °C
Temperatuur Min	-15 °C

Equivalent aan

Dupont Kalrez® Equivalent	Not Known
Freudenberg Simriz® Equivalent	Not Known
Greene Tweed Chemraz® Equivalent	Not Known
Parker Parafluor® Equivalent	Not Known

Specificaties

PPE Perlast® Equivalent PPE Perlast G80H

Trelleborg Isolast® Equivalent Not Known

Overige Specs

Alternatieve benaming FFPM – Dupont Kalrez

Chemische Benaming Perfluoroelastomer

Extra omschrijving O-ring 304.39x3.53 FFKM - FFPM

Merkmamen Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax

Technische Specs

Compressieset 28 %

Soortelijk Gewicht 2,55 (+/- 0,03) g/cm³

Treksterkte 13,2 MPa

Uitlaat Rek 100 %