



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 7.52x3.53 - FFKM - FFPM - Hoge Temp - FDA - EC1935/2004 - USP

<https://www.o-ring-stocks.eu/nl/o-ring-7.52x3.53-ffkm-ffpm-hoge-temp-fda-ec19352004-usp-class-vi-80-shore-a-wit-ors91111>

Specificaties

Productnummer	91111
Merk	Eurolast
Categorie	FFKM O-Rings - 80 Shore A - F808W95 - Wit
Materiaal	FFKM - FFPM
Kleur	Wit
Kleur	White

Basis Specificaties

Keurmerk	FDA 21 CFR 177.2400. EC1935/2004. USP Class VI. 3A-Sanitary Standard
----------	--

Alternatieve benaming	FFPM – Dupont Kalrez
Chemische Benaming	Perfluoroelastomer
Equivalent	Perlast® G80H . (G75 S)
Extra omschrijving	O-ring 7.52x3.53 FFKM
Maat in tekst	seven comma fifty two by three comma fifty three
Materiaal	FFKM - FFPM
Merknamen	Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax
Omschrijving-2	O-ring FFKM - FFPM 7.52x3.53
Verpakkingseenheid	O-ring

Alternative maat

AS568 Maat	AS 011
DIN 3771 Maat	7.52x3.53
SMS 1586 Maat	7.52 X 3.53

Basis Specificaties

CS (snoer dikte)	3.53 mm
Hardheid	80 Shore A
ID (binnendiameter)	7.52 mm
Temperatuur Max	300 °C
Temperatuur Min	-15 °C