



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 34.65x1.78 - FFKM - FFPM - Stoom - Heet Water - 75 Shore A - Zwart

<https://www.o-ring-stocks.eu/nl/o-ring-34.65x1.78-ffkm-ffpm-stoom-heet-water-75-shore-a-zwart-kalrez-1050lf-ors107721-equivalent>

### Specificaties

|               |                                     |
|---------------|-------------------------------------|
| Productnummer | 107721                              |
| Merk          | Eurolast                            |
| Categorie     | FFKM O-Rings - 75 Shore A - F758ZSR |
| Materiaal     | FFKM - FFPM                         |
| Kleur         | Zwart                               |
| Kleur         | Black                               |

### Basis Specificaties

|          |                  |
|----------|------------------|
| Keurmerk | Steam. Hot Water |
|----------|------------------|

|                       |                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Alternatieve benaming | FFPM – Dupont Kalrez                                                                                                                     |
| Chemische Benaming    | Perfluoroelastomer                                                                                                                       |
| Equivalent            | Kalrez® 1050LF . Chemraz® 555 . Chemraz® 605 .<br>Perflour® V8545-75 . Simriz® 487 . Isolast® J9512 .<br>Polymax P300B8ST . Evolast N8SR |

|                    |                                                                                                                                                       |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extra omschrijving | O-ring 34.65x1.78 FFKM                                                                                                                                |
| Maat in tekst      | thirty four comma sixty five by one comma seventy eight                                                                                               |
| Materiaal          | FFKM - FFPM                                                                                                                                           |
| Merknamen          | Evolast® - Chemraz® - Simriz® - Kalrez® - Spectrum -<br>Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® -<br>HPSealing® - Perfluor® - Polymax |
| Omschrijving-2     | O-ring FFKM - FFPM 34.65x1.78                                                                                                                         |
| Verpakkingseenheid | O-ring                                                                                                                                                |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 028       |
| DIN 3771 Maat | 34.65x1.78   |
| SMS 1586 Maat | 34.65 X 1.78 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 1.78 mm    |
| Hardheid            | 75 Shore A |
| ID (binnendiameter) | 34.65 mm   |
| Temperatuur Max     | 330 °C     |
| Temperatuur Min     | -15 °C     |