



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 5x2.5 - FFKM - FFPM - Stoom - Heet Water - 75 Shore A - Zwart -

<https://www.o-ring-stocks.eu/nl/o-ring-5x2.5-ffkm-ffpm-stoom-heet-water-75-shore-a-zwart-kalrez-1050lf-ors107407-equivalent>

Specificaties

Productnummer	107407
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F758ZSR
Materiaal	FFKM - FFPM
Kleur	Zwart
Kleur	Black

Basis Specificaties

Keurmerk	Steam. Hot Water
----------	------------------

Alternatieve benaming	FFPM – Dupont Kalrez
-----------------------	----------------------

Chemische Benaming	Perfluoroelastomer
--------------------	--------------------

Equivalent	Kalrez® 1050LF . Chemraz® 555 . Chemraz® 605 . Perflour® V8545-75 . Simriz® 487 . Isolast® J9512 . Polymax P300B8ST . Evolast N8SR
------------	--

Extra omschrijving	O-ring 5x2.5 FFKM
--------------------	-------------------

Maat in tekst	five zero by two comma fifty
---------------	------------------------------

Materiaal	FFKM - FFPM
-----------	-------------

Merknamen	Evolast® - Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax
-----------	---

Omschrijving-2	O-ring FFKM - FFPM 5x2.5
----------------	--------------------------

Verpakkingseenheid	O-ring
--------------------	--------

Alternative maat

AS568 Maat	AS 202
------------	--------

DIN 3771 Maat	5x2.5
---------------	-------

SMS 1586 Maat	5 X 2.5
---------------	---------

Basis Specificaties

CS (snoer dikte)	2.5 mm
------------------	--------

Hardheid	75 Shore A
----------	------------

ID (binnendiameter)	5 mm
---------------------	------

Temperatuur Max	330 °C
-----------------	--------

Temperatuur Min	-15 °C
-----------------	--------