



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 324x5.34 - FFKM - FFPM - Hoge Temp - 75 Shore A - Zwart - Kalrez®

<https://www.o-ring-stocks.eu/nl/o-ring-324x5.34-ffkm-ffpm-hoge-temp-75-shore-a-zwart-kalrez-4079-ors82021-equivalent>

Specificaties

Productnummer	82021
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F758Z96
Materiaal	FFKM - FFPM
Kleur	Zwart
Kleur	Black

Basis Specificaties

Keurmerk	General Purpose (+330°C)
----------	--------------------------

Alternatieve benaming	FFPM – Dupont Kalrez
Chemische Benaming	Perfluoroelastomer
Equivalent	Dupont Kalrez® 4079 - Greene Tweed Chemraz® 615 - PPE Perlast® G75B - Trelleborg Isolast® J8325 & Isolast® J9876

Extra omschrijving	O-ring 331x3.5 FFKM
Maat in tekst	three hundred and twenty four zero by five comma thirty four

Materiaal	FFKM - FFPM
Merknamen	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®

Omschrijving-2	O-ring FFKM - FFPM 324x5.34
Verpakkingseenheid	O-ring

Alternative maat

DIN 3771 Maat	324x5.34
SMS 1586 Maat	324 X 5.34

Basis Specificaties

CS (snoer dikte)	5.34 mm
Hardheid	75 Shore A
ID (binnendiameter)	324 mm
Temperatuur Max	330 °C
Temperatuur Min	-15 °C

Equivalent aan

Specificaties

Dupont Kalrez® Equivalent	Dupont Kalrez® 4079
Greene Tweed Chemraz® Equivalent	Greene Tweed Chemraz® 615
PPE Perlast® Equivalent	PPE Perlast® G75B
Trelleborg Isolast® Equivalent	Trelleborg Isolast® J8325 & Isolast® J9876