



O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 14.1x1.78 - FKM - 80 Shore A - Green - ORS166868

<https://www.o-ring-stocks.eu/nl/o-ring-14.1x1.78-fkm-80-shore-a-green-ors166868>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 166868                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Zwart |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | GROEN                            |
| Kleur         | Green                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                  |
| Chemische Benaming    | Fluorocarbon Rubber                           |
| Extra omschrijving    | O-ring 14.1x1.78 FKM - FPM - Viton            |
| Maat in tekst         | fourteen comma ten by one comma seventy eight |
| Materiaal             | FKM - FPM - Viton                             |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin       |
| Omschrijving-2        | O-ring FKM - FPM - Viton 14.1x1.78            |
| Verpakkingseenheid    | O-ring                                        |

### Alternative maat

|               |           |
|---------------|-----------|
| DIN 3771 Maat | 14.1x1.78 |
| ISO 3601 Maat | 14.1x1.78 |
| SMS 1586 Maat | 14.1x1.78 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 1.78 mm    |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 14.1 mm    |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |