



O-ring-Stocks.eu - Techniparts

Rondweg 26
8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 30.15x2.4 - FFKM - FFPM - Hoge Temp - 75 Shore A - Zwart -

<https://www.o-ring-stocks.eu/nl/o-ring-30.15x2.4-ffkm-ffpm-hoge-temp-75-shore-a-zwart-kalrez-4079-ors79098-equivalent>

Specificaties

Productnummer	79098
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F758Z96
Materiaal	FFKM - FFPM
Kleur	Zwart

Basis Specificaties

Keurmerk	General Purpose (+330°C)
Kleur	Black

Equivalent	Dupont Kalrez 4079, Freudenberg Simriz 498, Greene Tweed Chemraz 615, PPE Perlast G75B, Trelleborg Isolast J8325 & Isolast J9876,
------------	---

Materiaal	FFKM - FFPM
Omschrijving-2	O-ring FFKM - FFPM 30.15x2.4
Type Dichting	O-ring

Alternative maat

DIN 3771 Maat	30.15x2.4
Maat in tekst	thirty comma fifteen by two comma forty
SMS 1586 Maat	30.15 X 2.4

Basis Specificaties

CS (Snoer dikte)	2.4 mm
Hardheid	75 Shore A
ID (Binnendiameter)	30.15 mm
Temperatuur Max	330 °C
Temperatuur Min	-15 °C

Equivalent aan

Dupont Kalrez® Equivalent	Dupont Kalrez 4079
Freudenberg Simriz® Equivalent	Freudenberg Simriz 498
Greene Tweed Chemraz® Equivalent	Greene Tweed Chemraz 615
Parker Parafluor® Equivalent	Not Known
PPE Perlast® Equivalent	PPE Perlast G75B

Specificaties

Trelleborg Isolast® Equivalent	Trelleborg Isolast J8325 & Isolast J9876
--------------------------------	--

Overige Specs

Alternatieve benaming	FFPM – Dupont Kalrez
-----------------------	----------------------

Chemische Benaming	Perfluoroelastomer
--------------------	--------------------

Extra omschrijving	O-ring 56.5x3.5 FFKM - FFPM
--------------------	-----------------------------

Merknamen	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®
-----------	--

Technische Specs

Compressieset	19,5 %
---------------	--------

Soortelijk Gewicht	1,98 (+/- 0.03) g/cm ³
--------------------	-----------------------------------

Treksterkte	17,8 MPa
-------------	----------

Ultimale Rek	152 %
--------------	-------