



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 6.07x1.78 - FFKM - FFPM - Hoge Temp - 75 Shore A - Zwart - Kalrez®

<https://www.o-ring-stocks.eu/nl/o-ring-6.07x1.78-ffkm-ffpm-hoge-temp-75-shore-a-zwart-kalrez-4079-ors71317-equivalent>

Specificaties

Productnummer	71317
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F758Z96
Materiaal	FFKM - FFPM
Kleur	Zwart
Kleur	Black

Basis Specificaties

Keurmerk	General Purpose (+330°C)
----------	--------------------------

Alternatieve benaming	FFPM – Dupont Kalrez
Chemische Benaming	Perfluoroelastomer
Equivalent	Dupont Kalrez® 4079 - Greene Tweed Chemraz® 615 - PPE Perlast® G75B - Trelleborg Isolast® J8325 & Isolast® J9876

Extra omschrijving	O-ring 231x7 FFKM
Maat in tekst	six comma seven by one comma seventy eight
Materiaal	FFKM - FFPM
Merkenamen	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®
Omschrijving-2	O-ring FFKM - FFPM 6.07x1.78
Verpakkingseenheid	O-ring

Alternative maat

AS568 Maat	AS 010
DIN 3771 Maat	6.07x1.78
SMS 1586 Maat	6.07 X 1.78

Basis Specificaties

CS (snoer dikte)	1.78 mm
Hardheid	75 Shore A
ID (binnendiameter)	6.07 mm
Temperatuur Max	330 °C
Temperatuur Min	-15 °C

Equivalent aan

Specificaties

Dupont Kalrez® Equivalent	Dupont Kalrez® 4079
Greene Tweed Chemraz® Equivalent	Greene Tweed Chemraz® 615
PPE Perlast® Equivalent	PPE Perlast® G75B
Trelleborg Isolast® Equivalent	Trelleborg Isolast® J8325 & Isolast® J9876