



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 177.4x3.53 - FFKM - FFPM - FDA - USP Class VI - 75 Shore A - Zwart

<https://www.o-ring-stocks.eu/nl/o-ring-177.4x3.53-ffkm-ffpm-fda-usp-class-vi-75-shore-a-zwart-kalrez-6230-ors85573-equivalent>

Specificaties

Productnummer	85573
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F757ZFD
Materiaal	FFKM - FFPM
Kleur	Zwart
Kleur	Black

Basis Specificaties

Keurmerk	FDA 21 CFR 177.2400. USP Class VI. 3A-Sanitary Standard
----------	---

Alternatieve benaming	FFPM – Dupont Kalrez
Chemische Benaming	Perfluoroelastomer
Equivalent	Kalrez® 6230. Chemraz® SD625. Evolast N7FD. Polymax P260B8FDA. Polymax P230W7USP
Extra omschrijving	O-ring 484.4x5.7 FFKM
Maat in tekst	one hundred and seventy seven comma forty by three comma fifty three
Materiaal	FFKM - FFPM
Merknamen	Evolast® - Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax
Omschrijving-2	O-ring FFKM - FFPM 177.4x3.53
Verpakkingseenheid	O-ring

Alternative maat

AS568 Maat	AS 141
DIN 3771 Maat	177.4x3.53
SMS 1586 Maat	177.4 X 3.53

Basis Specificaties

CS (snoer dikte)	3.53 mm
Hardheid	75 Shore A
ID (binnendiameter)	177.4 mm
Temperatuur Max	270 °C

Specificaties

Temperatuur Min	-20 °C
-----------------	--------