



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 170x5 - FFKM - FFPM - FDA - USP Class VI - 75 Shore A - Zwart -

<https://www.o-ring-stocks.eu/nl/o-ring-170x5-ffkm-ffpm-fda-usp-class-vi-75-shore-a-zwart-kalrez-6230-ors85544-equivalent>

Specificaties

Productnummer 85544

Merk Eurolast

Categorie FFKM O-Rings - 75 Shore A - F757ZFD

Materiaal FFKM - FFPM

Kleur Zwart

Kleur Black

Basis Specificaties

Keurmerk FDA 21 CFR 177.2400. USP Class VI. 3A-Sanitary Standard

Alternatieve benaming FFPM – Dupont Kalrez

Chemische Benaming Perfluoroelastomer

Equivalent Kalrez® 6230. Chemraz® SD625. Evolast N7FD. Polymax P260B8FDA. Polymax P230W7USP

Extra omschrijving O-ring 469.9x3.53 FFKM

Maat in tekst one hundred and seventy zero by five zero

Materiaal FFKM - FFPM

Merknamen Evolast® - Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax

Omschrijving-2 O-ring FFKM - FFPM 170x5

Verpakkingseenheid O-ring

Alternative maat

DIN 3771 Maat 170x5

SMS 1586 Maat 170 X 5

Basis Specificaties

CS (snoer dikte) 5 mm

Hardheid 75 Shore A

ID (binnendiameter) 170 mm

Temperatuur Max 270 °C

Temperatuur Min -20 °C