



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 253.4x6.99 - FFKM - FFPM - FDA - EC1935/2004 - USP Class VI - 70

<https://www.o-ring-stocks.eu/nl/o-ring-253.4x6.99-ffkm-ffpm-fda-ec19352004-usp-class-vi-70-shore-a-wit-kalrez-6880-ors179081-equivalent>

Specificaties

Productnummer	179081
Merk	Eurolast
Categorie	FFKM O-Rings - 70 Shore A - B794 - Wit
Materiaal	FFKM - FFPM
Kleur	WIT
Kleur	White

Basis Specificaties

Keurmerk	FDA 21 CFR 177.2400. EC1935/2004. USP Class VI. 3A-Sanitary Standard
----------	--

Alternatieve benaming	FFPM – Dupont Kalrez
Chemische Benaming	Perfluoroelastomer
Equivalent	Kalrez® 6880 - Kalrez® 6221 - Perlast® G74S
Extra omschrijving	O-ring 253.4x6.99 FFKM
Maat in tekst	two hundred and fifty three comma forty by six comma ninety nine
Materiaal	FFKM - FFPM
Merknamen	Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax
Omschrijving-2	O-ring FFKM - FFPM 253.4x6.99
Verpakkingseenheid	O-ring

Alternative maat

AS568 Maat	AS 377
DIN 3771 Maat	253.4 x 6.99
SMS 1586 Maat	253.4x6.99

Basis Specificaties

CS (snoer dikte)	6.99 mm
Hardheid	70 Shore A
ID (binnendiameter)	253.4 mm
Temperatuur Max	270 °C
Temperatuur Min	-20 °C