



O-ring-Stocks.eu - Techniparts

Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 62.78x5.33 - FEP-FKM - FDA - ORS173158

<https://www.o-ring-stocks.eu/nl/o-ring-62.78x5.33-fep-fkm-fda-ors173158>

### Specificaties

|               |                     |
|---------------|---------------------|
| Productnummer | 173158              |
| Merk          | Eurolast            |
| Categorie     | FEP - Viton O-Rings |
| Materiaal     | FKM - FPM - Viton   |
| Kleur         | Zwart               |
| Kleur         | Black               |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                             |
| Chemische Benaming    | Fluorocarbon Rubber                                      |
| Extra omschrijving    | O-ring 62.78x5.33 FKM - FPM - Viton                      |
| Maat in tekst         | sixty two comma seventy eight by five comma thirty three |
| Materiaal             | FKM - FPM - Viton                                        |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                  |
| Omschrijving-2        | O-ring FKM - FPM - Viton 62.78x5.33                      |
| Verpakkingseenheid    | O-ring                                                   |

### Alternative maat

|               |            |
|---------------|------------|
| AS568 Maat    | AS 114     |
| DIN 3771 Maat | 62.78x5.33 |
| ISO 3601 Maat | 62.78x5.33 |
| SMS 1586 Maat | 62.78x5.33 |

### Basis Specificaties

|                              |          |
|------------------------------|----------|
| CS (snoer dikte)             | 5.33 mm  |
| ID (binnendiameter)          | 62.78 mm |
| Temperatuur Max              | 205 °C   |
| Temperatuur Min              | -20 °C   |
| Tolerantie (CS) DIN 7715-M2F | ± 1,00   |
| Tolerantie (ID) DIN 7715-M2F | ± 0,95   |