



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 162x3 - FEP-FKM - FDA - ORS173253

<https://www.o-ring-stocks.eu/nl/o-ring-162x3-fep-fkm-fda-ors173253>

### Specificaties

|               |                     |
|---------------|---------------------|
| Productnummer | 173253              |
| Merk          | Eurolast            |
| Categorie     | FEP - Viton O-Rings |
| Materiaal     | FKM - FPM - Viton   |
| Kleur         | Zwart               |
| Kleur         | Black               |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                              |
|-----------------------|----------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                 |
| Chemische Benaming    | Fluorocarbon Rubber                          |
| Extra omschrijving    | O-ring 162x3 FKM - FPM - Viton               |
| Maat in tekst         | one hundred and sixty two zero by three zero |
| Materiaal             | FKM - FPM - Viton                            |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin      |
| Omschrijving-2        | O-ring FKM - FPM - Viton 162x3               |
| Verpakkingseenheid    | O-ring                                       |

### Alternative maat

|               |       |
|---------------|-------|
| DIN 3771 Maat | 162x3 |
| ISO 3601 Maat | 162x3 |
| SMS 1586 Maat | 162x3 |

### Basis Specificaties

|                              |        |
|------------------------------|--------|
| CS (snoer dikte)             | 3 mm   |
| ID (binnendiameter)          | 162 mm |
| Temperatuur Max              | 205 °C |
| Temperatuur Min              | -20 °C |
| Tolerantie (CS) DIN 7715-M2F | ± 0,10 |
| Tolerantie (ID) DIN 7715-M2F | ± 0,40 |