



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 21.5x2 - FEP-FKM - FPM - Viton - FDA - ORS113625

<https://www.o-ring-stocks.eu/nl/o-ring-21.5x2-fep-fkm-fpm-viton-fda-ors113625>

### Specificaties

|               |                       |
|---------------|-----------------------|
| Productnummer | 6522730               |
| Merk          | Eurolast              |
| Categorie     | FEP - Viton O-Rings   |
| Materiaal     | FEP-FKM - FPM - Viton |
| Kleur         | Zwart                 |
| Kleur         | Black                 |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                                    |
|-----------------------|----------------------------------------------------|
| Alternatieve benaming | FEP - Viton® - FKM / FEP encapsulated Viton® - FKM |
| Chemische Benaming    | Teflon® fluoropolymer - Viton                      |
| Extra omschrijving    | O-ring 21.5x2 FEP-FPM - Viton                      |
| Maat in tekst         | twenty one comma fifty by two zero                 |
| Materiaal             | FEP-FKM - FPM - Viton                              |
| Merksnamen            | Teflex FEP-O-SEAL®                                 |
| Omschrijving-2        | O-ring FEP-FKM - FPM - Viton 21.5x2                |
| Verpakkingseenheid    | O-ring                                             |

### Alternative maat

|               |          |
|---------------|----------|
| DIN 3771 Maat | 21.5x2   |
| SMS 1586 Maat | 21.5 X 2 |

### Basis Specificaties

|                              |         |
|------------------------------|---------|
| CS (snoer dikte)             | 2 mm    |
| ID (binnendiameter)          | 21.5 mm |
| Temperatuur Max              | 205 °C  |
| Tolerantie (CS) DIN 7715-M2F | ± 0,12  |
| Tolerantie (ID) DIN 7715-M2F | N/A     |