



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 29.82x2.62 - FEP-FKM - FPM - Viton - FDA - ORS35337

<https://www.o-ring-stocks.eu/nl/o-ring-29.82x2.62-fep-fkm-fpm-viton-fda-ors35337>

### Specificaties

|               |                       |
|---------------|-----------------------|
| Productnummer | 288507                |
| Merk          | Eurolast              |
| Categorie     | FEP - Viton O-Rings   |
| Materiaal     | FEP-FKM - FPM - Viton |
| Kleur         | Zwart                 |
| Kleur         | Black                 |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                                     |
|-----------------------|-----------------------------------------------------|
| Alternatieve benaming | FEP - Viton® - FKM / FEP encapsulated Viton® - FKM  |
| Chemische Benaming    | Teflon® fluoropolymer - Viton                       |
| Extra omschrijving    | O-ring 29.82x2.62 FEP-FPM - Viton                   |
| Maat in tekst         | twenty nine comma eighty two by two comma sixty two |
| Materiaal             | FEP-FKM - FPM - Viton                               |
| Merknamen             | Teflex FEP-O-SEAL®                                  |
| Omschrijving-2        | O-ring FEP-FKM - FPM - Viton 29.82x2.62             |
| Verpakkingseenheid    | O-ring                                              |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 123       |
| DIN 3771 Maat | 29.82x2.62   |
| SMS 1586 Maat | 29.82 X 2.62 |

### Basis Specificaties

|                              |          |
|------------------------------|----------|
| CS (snoer dikte)             | 2.62 mm  |
| ID (binnendiameter)          | 29.82 mm |
| Temperatuur Max              | 205 °C   |
| Tolerantie (CS) DIN 7715-M2F | ± 0,10   |
| Tolerantie (ID) DIN 7715-M2F | ± 0,35   |