



## O-ring 459.2x5.7 - FEP-VMQ - MVQ - Silicone - FDA - ORS113068

<https://www.o-ring-stocks.eu/nl/o-ring-459.2x5.7-fep-vmq-mvq-silicone-fda-ors113068>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 6522138                  |
| Merk          | Eurolast                 |
| Categorie     | FEP - Silicone O-Rings   |
| Materiaal     | FEP-VMQ - MVQ - Silicone |
| Kleur         | Rood                     |
| Kleur         | Red                      |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                                                             |
|-----------------------|-----------------------------------------------------------------------------|
| Alternatieve benaming | FEP-VMQ / VMQ - FEP Encapsulated / FEP-Silicone / Silicone FEP Encapsulated |
| Chemische Benaming    | Teflon® fluoropolymer - Silicone                                            |
| Extra omschrijving    | O-ring 459.2x5.7 FEP-VMQ - Silicone                                         |
| Maat in tekst         | four hundred and fifty nine comma twenty by five comma seventy              |
| Materiaal             | FEP-VMQ - MVQ - Silicone                                                    |
| Merknamen             | Teflex FEP-O-SEAL®                                                          |
| Omschrijving-2        | O-ring FEP-VMQ - MVQ - Silicone 459.2x5.7                                   |
| Verpakkingseenheid    | O-ring                                                                      |

### Alternative maat

|               |             |
|---------------|-------------|
| DIN 3771 Maat | 459.2x5.7   |
| SMS 1586 Maat | 459.2 X 5.7 |

### Basis Specificaties

|                              |           |
|------------------------------|-----------|
| CS (snoer dikte)             | 5.7 mm    |
| ID (binnendiameter)          | 459.2 mm  |
| Temperatuur Max              | 205 °C    |
| Tolerantie (CS) DIN 7715-M2F | ± 0,25 mm |
| Tolerantie (ID) DIN 7715-M2F | ± 1,29 mm |