



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 120.02x6.99 - VMQ - MVQ - Silicone - FDA - EC1935/2004 - 70 Shore

<https://www.o-ring-stocks.eu/nl/o-ring-120.02x6.99-vmq-mvq-silicone-fda-ec19352004-70-shore-a-rood-ors16158>

### Specificaties

|               |                                       |
|---------------|---------------------------------------|
| Productnummer | 16158                                 |
| Merk          | Eurolast                              |
| Categorie     | VMQ O-Rings - 70 Shore A - Rood - FDA |
| Materiaal     | VMQ - MVQ - Silicone                  |
| Kleur         | Rood                                  |
| Kleur         | Red                                   |

### Basis Specificaties

|          |                                   |
|----------|-----------------------------------|
| Keurmerk | FDA 21 CFR 177.2600 – EC1935/2004 |
|----------|-----------------------------------|

|                       |                                                           |
|-----------------------|-----------------------------------------------------------|
| Alternatieve benaming | Silicone Rubber - PVMQ                                    |
| Chemische Benaming    | Vinyl Methyl Silicone                                     |
| Extra omschrijving    | O-ring 120.02x6.99 VMQ - Silicone                         |
| Maat in tekst         | one hundred and twenty comma two by six comma ninety nine |
| Materiaal             | Silicone - VMQ - MVQ                                      |
| Merknamen             | Eriks - Wacker - Eastern Seals - and BlueStar             |
| Omschrijving-2        | O-ring VMQ - MVQ - Silicone 120.02x6.99                   |
| Verpakkingseenheid    | O-ring                                                    |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 427        |
| DIN 3771 Maat | 120.02x6.99   |
| SMS 1586 Maat | 120.02 X 6.99 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 6.99 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 120.02 mm  |
| Temperatuur Max     | 210 °C     |
| Temperatuur Min     | -50 °C     |