



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 98.02x3.53 - VMQ - MVQ - Silicone - FDA - EC1935/2004 - 70 Shore A

<https://www.o-ring-stocks.eu/nl/o-ring-98.02x3.53-vmq-mvq-silicone-fda-ec19352004-70-shore-a-rood-ors10157>

### Specificaties

|               |                                       |
|---------------|---------------------------------------|
| Productnummer | 10157                                 |
| EAN           | 6150546889899                         |
| Merk          | Eurolast                              |
| Categorie     | VMQ O-Rings - 70 Shore A - Rood - FDA |
| Materiaal     | VMQ - MVQ - Silicone                  |
| Kleur         | Rood                                  |
| Kleur         | Red                                   |

### Basis Specificaties

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| Keurmerk              | FDA 21 CFR 177.2600 – EC1935/2004                 |
| Alternatieve benaming | Silicone Rubber - PVMQ                            |
| Chemische Benaming    | Vinyl Methyl Silicone                             |
| Extra omschrijving    | O-ring 98.02x3.53 VMQ - Silicone                  |
| Maat in tekst         | ninety eight comma two by three comma fifty three |
| Materiaal             | Silicone - VMQ - MVQ                              |
| Merkenamen            | Eriks - Wacker - Eastern Seals - and BlueStar     |
| Omschrijving-2        | O-ring VMQ - MVQ - Silicone 98.02x3.53            |
| Verpakkingseenheid    | O-ring                                            |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 241       |
| DIN 3771 Maat | 98.02x3.53   |
| SMS 1586 Maat | 98.02 X 3.53 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.53 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 98.02 mm   |
| Temperatuur Max     | 210 °C     |
| Temperatuur Min     | -50 °C     |