



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-Ring 82.28x1.78 - VMQ - MVQ - Silicone - 60 Shore A - Rood - ORS131386

<https://www.o-ring-stocks.eu/nl/o-ring-82.28x1.78-vmq-mvq-silicone-60-shore-a-rood-ors131386>

### Specificaties

|               |                                             |
|---------------|---------------------------------------------|
| Productnummer | 131386                                      |
| Merk          | Eurolast                                    |
| Categorie     | VMQ - MVQ - Silicone - O-Rings - 60 Shore A |
| Materiaal     | VMQ - MVQ - Silicone                        |
| Kleur         | Rood                                        |
| Kleur         | Red                                         |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Alternatieve benaming | Silicone Rubber - PVMQ                                   |
| Chemische Benaming    | Vinyl Methyl Silicone                                    |
| Extra omschrijving    | O-Ring 82.28x1.78 VMQ - MVQ - Silicone                   |
| Maat in tekst         | eighty two comma twenty eight by one comma seventy eight |
| Materiaal             | Silicone - VMQ - MVQ                                     |
| Merknamen             | Eriks - Wacker - Eastern Seals - and BlueStar            |
| Omschrijving-2        | O-ring VMQ - MVQ - Silicone 82.28x1.78                   |
| Verpakkingseenheid    | O-ring                                                   |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 042       |
| DIN 3771 Maat | 82.28x1.78   |
| SMS 1586 Maat | 82.28 X 1.78 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 1.78 mm    |
| Hardheid            | 60 Shore A |
| ID (binnendiameter) | 82.28 mm   |
| Temperatuur Max     | 210 °C     |
| Temperatuur Min     | -50 °C     |