



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-Ring 20.22x3.53 - EPDM - 80 Shore A - Zwart - Sulfur - ORS118651

<https://www.o-ring-stocks.eu/nl/o-ring-20.22x3.53-epdm-80-shore-a-zwart-sulfur-ors118651>

### Specificaties

|               |                           |
|---------------|---------------------------|
| Productnummer | 118651                    |
| Merk          | Eurolast                  |
| Categorie     | EPDM O-Rings - 80 Shore A |
| Materiaal     | EPDM                      |
| Kleur         | Zwart                     |
| Kleur         | Black                     |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                    |                                                    |
|--------------------|----------------------------------------------------|
| Chemische Benaming | Ethylene propylene diene monomer                   |
| Extra omschrijving | O-Ring 20.22x3.53 EPDM                             |
| Maat in tekst      | twenty comma twenty two by three comma fifty three |
| Materiaal          | EPDM                                               |
| Merknamen          | Dow Chemical - ExxonMobil - and Lion Elastomers    |
| Omschrijving-2     | O-ring EPDM 20.22x3.53                             |
| Verpakkingseenheid | O-ring                                             |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 211       |
| DIN 3771 Maat | 20.22x3.53   |
| SMS 1586 Maat | 20.22 X 3.53 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.53 mm    |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 20.22 mm   |
| Temperatuur Max     | 150 °C     |
| Temperatuur Min     | -40 °C     |
| Vulkanisatie        | Sulfur     |