



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-Ring 47.29x2.62 - EPDM - 80 Shore A - Zwart - PEROX - ORS118759

<https://www.o-ring-stocks.eu/nl/o-ring-47.29x2.62-epdm-80-shore-a-zwart-perox-ors118759>

### Specificaties

|               |                                   |
|---------------|-----------------------------------|
| Productnummer | 118759                            |
| Merk          | Eurolast                          |
| Categorie     | EPDM O-Rings - 80 Shore A - Perox |
| Materiaal     | EPDM                              |
| Kleur         | Zwart                             |
| Kleur         | Black                             |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                    |                                                      |
|--------------------|------------------------------------------------------|
| Chemische Benaming | Ethylene propylene diene monomer                     |
| Extra omschrijving | O-Ring 47.29x2.62 EPDM                               |
| Maat in tekst      | forty seven comma twenty nine by two comma sixty two |
| Materiaal          | EPDM                                                 |
| Merknamen          | Dow Chemical - ExxonMobil - and Lion Elastomers      |
| Omschrijving-2     | O-ring EPDM 47.29x2.62                               |
| Verpakkingseenheid | O-ring                                               |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 134       |
| DIN 3771 Maat | 47.29x2.62   |
| SMS 1586 Maat | 47.29 X 2.62 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 2.62 mm    |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 47.29 mm   |
| Temperatuur Max     | 150 °C     |
| Temperatuur Min     | -40 °C     |
| Vulkanisatie        | Peroxide   |