



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 354.97x5.33 - EDPM - Zwavel -70 Shore A - Zwart - ORS11282

<https://www.o-ring-stocks.eu/nl/o-ring-354.97x5.33-edpm-zwavel-70-shore-a-zwart-ors11282>

### Specificaties

|               |                           |
|---------------|---------------------------|
| Productnummer | 11282                     |
| EAN           | 6150549990981             |
| Merk          | Eurolast                  |
| Categorie     | EPDM O-Rings - 70 Shore A |
| Materiaal     | EPDM                      |
| Kleur         | Zwart                     |
| Kleur         | Black                     |

### Basis Specificaties

|                    |                                                                            |
|--------------------|----------------------------------------------------------------------------|
| Keurmerk           | None                                                                       |
| Chemische Benaming | Ethylene propylene diene monomer                                           |
| Extra omschrijving | O-ring 354.97x5.33 EPDM                                                    |
| Maat in tekst      | three hundred and fifty four comma ninety seven by five comma thirty three |
| Materiaal          | EPDM                                                                       |
| Merknamen          | Dow Chemical - ExxonMobil - and Lion Elastomers                            |
| Omschrijving-2     | O-ring EPDM 354.97x5.33                                                    |
| Verpakkingseenheid | O-ring                                                                     |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 383        |
| DIN 3771 Maat | 354.97x5.33   |
| SMS 1586 Maat | 354.97 X 5.33 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.33 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 354.97 mm  |
| Temperatuur Max     | 125 °C     |
| Temperatuur Min     | -40 °C     |
| Vulkanisatie        | Sulfur     |