



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 148.82x3.53 - EDPM - Zwavel -70 Shore A - Zwart - ORS11158

<https://www.o-ring-stocks.eu/nl/o-ring-148.82x3.53-edpm-zwavel-70-shore-a-zwart-ors11158>

### Specificaties

|               |                           |
|---------------|---------------------------|
| Productnummer | 11158                     |
| EAN           | 6150546891854             |
| Merk          | Eurolast                  |
| Categorie     | EPDM O-Rings - 70 Shore A |
| Materiaal     | EPDM                      |
| Kleur         | Zwart                     |
| Kleur         | Black                     |

### Basis Specificaties

|                    |                                                                         |
|--------------------|-------------------------------------------------------------------------|
| Keurmerk           | None                                                                    |
| Chemische Benaming | Ethylene propylene diene monomer                                        |
| Extra omschrijving | O-ring 148.82x3.53 EPDM                                                 |
| Maat in tekst      | one hundred and forty eight comma eighty two by three comma fifty three |
| Materiaal          | EPDM                                                                    |
| Merknamen          | Dow Chemical - ExxonMobil - and Lion Elastomers                         |
| Omschrijving-2     | O-ring EPDM 148.82x3.53                                                 |
| Verpakkingseenheid | O-ring                                                                  |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 257        |
| DIN 3771 Maat | 148.82x3.53   |
| SMS 1586 Maat | 148.82 X 3.53 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.53 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 148.82 mm  |
| Temperatuur Max     | 125 °C     |
| Temperatuur Min     | -40 °C     |
| Vulkanisatie        | Sulfur     |