



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 66.04x1.78 - EPDM - Peroxide - FDA - EC1935/2004 - 70 Shore A -

<https://www.o-ring-stocks.eu/o-ring-66.04x1.78-epdm-peroxide-fda-ec19352004-70-shore-a-black-ors172553>

### Specificaties

|               |                                 |
|---------------|---------------------------------|
| Productnummer | 172553                          |
| Merk          | Eurolast                        |
| Categorie     | EPDM O-Rings - 70 Shore A - FDA |
| Materiaal     | EPDM                            |
| Kleur         | ZWART                           |
| Color         | Black                           |

### Core Spec's

|          |                                   |
|----------|-----------------------------------|
| Approval | FDA 21 CFR 177.2600 – EC1935/2004 |
|----------|-----------------------------------|

|                |                                                 |
|----------------|-------------------------------------------------|
| Chemical Name  | Ethylene propylene diene monomer                |
| Description 2  | O-ring EPDM 66.04x1.78                          |
| Material       | EPDM                                            |
| Packaging Unit | O-ring                                          |
| Product name   | O-ring 66.04x1.78 EPDM                          |
| Size in text   | sixty six comma four by one comma seventy eight |
| Trade names    | Dow Chemical - ExxonMobil - and Lion Elastomers |

### Alternative Size

|                     |            |
|---------------------|------------|
| DIN 3771 Size Chart | 66.04x1.78 |
| ISO 3601 Size Chart | 66.04x1.78 |
| SMS 1586 Size chart | 66.04x1.78 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 1.78 mm    |
| Hardness            | 70 Shore A |
| ID (inner diameter) | 66.04 mm   |
| Temperature Max     | 150 °C     |
| Temperature Min     | -50 °C     |
| Vulcanisation       | Peroxide   |