



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 20.29x2.62 - ACM - 70 Shore A - Black - ORS35508

<https://www.o-ring-stocks.eu/o-ring-20.29x2.62-acm-70-shore-a-black-ors35508>

Specificaties

Productnummer 35508

Merk Eurolast

Categorie ACM O-Rings

Materiaal ACM

Kleur Zwart

Color Black

Core Spec's

Approval None

Chemical Name PolyAcrylate Rubber / alkyl acrylate copolymer

Description 2 O-ring ACM 20.29x2.62

Material ACM

Packaging Unit O-ring

Product name O-ring 20.29x2.62 ACM

Size in text twenty comma twenty nine by two comma sixty two

Trade names HyTemp

Alternative Size

AS568 Size Chart AS 117

DIN 3771 Size Chart 20.29x2.62

SMS 1586 Size chart 20.29 X 2.62

Core Spec's

CS (Cross Section) 2.62 mm

Hardness 70 Shore A

ID (inner diameter) 20.29 mm

Temperature Max 150 °C

Temperature Min -20 °C

Pluspunten

+ Resistance to petroleum fuels and oils, automatic transmission fluid, type A power steering fluid. Good resistance to mineral oil, sunlight, oxygen, and ozone.

Minpunten

- Cannot be used in alcohol, alkalis, glycol based brake fluids, EP fluids, chlorinated hydrocarbons, gear oils, glycol based brake fluids, hydrocarbons, water or steam (above 275°F), acids and amines. Lower water compatibility, cold flexibility, strength, and compression set resistance t