



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 20.35x1.78 - ACM - 70 Shore A - Black - ORS35509

<https://www.o-ring-stocks.eu/o-ring-20.35x1.78-acm-70-shore-a-black-ors35509>

Specificaties

Productnummer	35509
Merk	Eurolast
Categorie	ACM O-Rings
Materiaal	ACM
Kleur	Zwart
Color	Black

Core Spec's

Approval	None
----------	------

Chemical Name	PolyAcrylate Rubber / alkyl acrylate copolymer
Description 2	O-ring ACM 20.35x1.78
Material	ACM
Packaging Unit	O-ring
Product name	O-ring 20.35x1.78 ACM
Size in text	twenty comma thirty five by one comma seventy eight
Trade names	HyTemp

Alternative Size

AS568 Size Chart	AS 019
DIN 3771 Size Chart	20.35x1.78
SMS 1586 Size chart	20.35 X 1.78

Core Spec's

CS (Cross Section)	1.78 mm
Hardness	70 Shore A
ID (inner diameter)	20.35 mm
Temperature Max	150 °C
Temperature Min	-20 °C

Pluspunten

+ Resistance to petroleum fuels and oils, automatic transmission fluid, type A power steering fluid. Good resistance to mineral oil, sunlight, oxygen, and ozone.

Minpunten

- Cannot be used in alcohol, alkalis, glycol based brake fluids, EP fluids, chlorinated hydrocarbons, gear oils, glycol based brake fluids, hydrocarbons, water or steam (above 275°F), acids and amines. Lower water compatibility, cold flexibility, strength, and compression set resistance t