



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 443.36x6.99 - CR - Neoprene - 70 Shore A - Black - ORS48448

<https://www.o-ring-stocks.eu/o-ring-443.36x6.99-cr-neoprene-70-shore-a-black-ors48448>

### Specificaties

|               |               |
|---------------|---------------|
| Productnummer | 48448         |
| Merk          | Eurolast      |
| Categorie     | CR O-Rings    |
| Materiaal     | CR - Neoprene |
| Kleur         | Zwart         |
| Color         | Black         |

### Core Spec's

|          |      |
|----------|------|
| Approval | None |
|----------|------|

|                   |                                                                        |
|-------------------|------------------------------------------------------------------------|
| Alternative names | Neoprene                                                               |
| Chemical Name     | Chloroprene rubber / chlorobutadiene rubber                            |
| Description 2     | O-ring CR - Neoprene 443.36x6.99                                       |
| Material          | CR - Neoprene                                                          |
| Packaging Unit    | O-ring                                                                 |
| Product name      | O-ring 443.36x6.99 CR - Neopreen                                       |
| Size in text      | four hundred and forty three comma thirty six by six comma ninety nine |
| Trade names       | Neoprene                                                               |

### Alternative Size

|                     |               |
|---------------------|---------------|
| AS568 Size Chart    | AS 464        |
| DIN 3771 Size Chart | 443.36x6.99   |
| SMS 1586 Size chart | 443.36 X 6.99 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 6.99 mm    |
| Hardness            | 70 Shore A |
| ID (inner diameter) | 443.36 mm  |
| Temperature Max     | 100 °C     |
| Temperature Min     | -40 °C     |