



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 129.8x3.53 - HNBR - AED - 90 Shore A - Black - ORS176116

<https://www.o-ring-stocks.eu/o-ring-129.8x3.53-hnbr-aed-90-shore-a-black-ors176116>

### Specificaties

|               |                                   |
|---------------|-----------------------------------|
| Productnummer | 176116                            |
| Merk          | Eurolast                          |
| Categorie     | HNBR O-Rings - 70 Shore A - Black |
| Materiaal     | HNBR - Buna                       |
| Kleur         | ZWART                             |
| Color         | Black                             |

### Core Spec's

|          |     |
|----------|-----|
| Approval | AED |
|----------|-----|

|                   |                                                                     |
|-------------------|---------------------------------------------------------------------|
| Alternative names | Hydrogenated Nitrile Butadiene Rubber                               |
| Chemical Name     | Hydrogenated nitrile rubber                                         |
| Description 2     | O-ring HNBR - 129.8x3.53                                            |
| Material          | HNBR                                                                |
| Packaging Unit    | O-ring                                                              |
| Product name      | O-ring 129.8x3.53                                                   |
| Size in text      | one hundred and twenty nine comma eighty by three comma fifty three |
| Trade names       | Lanxess - Zeon - and LG Chem                                        |

### Alternative Size

|                     |              |
|---------------------|--------------|
| AS568 Size Chart    | AS 118       |
| DIN 3771 Size Chart | 129.8 x 3.53 |
| SMS 1586 Size chart | 129.8x3.53   |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 3.53 mm    |
| Hardness            | 90 Shore A |
| ID (inner diameter) | 129.8 mm   |
| Temperature Max     | 150 °C     |
| Temperature Min     | -25 °C     |