



O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 179.5x8.4 - FKM - FPM - Viton - 80 Shore A - Brown - ORS35971

<https://www.o-ring-stocks.eu/o-ring-179.5x8.4-fkm-fpm-viton-80-shore-a-brown-ors35971>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 35971                            |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Brown |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Bruin                            |
| Color         | Brown                            |

### Core Spec's

|          |      |
|----------|------|
| Approval | None |
|----------|------|

|                   |                                                               |
|-------------------|---------------------------------------------------------------|
| Alternative names | Viton® - FKM                                                  |
| Chemical Name     | Fluorocarbon Rubber                                           |
| Description 2     | O-ring FKM - FPM - Viton 179.5x8.4                            |
| Material          | FKM - FPM - Viton                                             |
| Packaging Unit    | O-ring                                                        |
| Product name      | O-ring 179.5x8.4 FPM - Viton                                  |
| Size in text      | one hundred and seventy nine comma fifty by eight comma forty |
| Trade names       | Viton® - Du Pont - 3M - Solvay - Daikin                       |

### Alternative Size

|                       |             |
|-----------------------|-------------|
| DIN 3771 Size Chart   | 179.5x8.4   |
| JIS B 2401 Size Chart | JIS P180    |
| SMS 1586 Size chart   | 179.5 X 8.4 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 8.4 mm     |
| Hardness            | 80 Shore A |
| ID (inner diameter) | 179.5 mm   |
| Temperature Max     | 205 °C     |
| Temperature Min     | -20 °C     |