



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 146.05x5.33 - NBR - Nitrile - 70 Shore A - Black - ORS2048

<https://www.o-ring-stocks.eu/o-ring-146.05x5.33-nbr-nitrile-70-shore-a-black-ors2048>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 2048                     |
| EAN           | 6150549225236            |
| Merk          | Eurolast                 |
| Categorie     | NBR O-Rings - 70 Shore A |
| Materiaal     | Nitrile NBR-Buna         |
| Kleur         | Zwart                    |
| Color         | Black                    |

### Core Spec's

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Approval          | None                                                            |
| Alternative names | Nitrile Rubber - NBR                                            |
| Chemical Name     | Acrylonitrile butadiene rubber                                  |
| Description 2     | O-ring NBR - Nitrile 146.05x5.33                                |
| Material          | NBR - Nitrile                                                   |
| Packaging Unit    | O-ring                                                          |
| Product name      | O-ring 146.05x5.33 Nitrile NBR                                  |
| Size in text      | one hundred and forty six comma five by five comma thirty three |
| Trade names       | Lanxess - Zeon - and LG Chem                                    |

### Alternative Size

|                     |               |
|---------------------|---------------|
| BS 1806 Size Chart  | BS 869        |
| DIN 3771 Size Chart | 146.05x5.33   |
| SMS 1586 Size chart | 146.05 X 5.33 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 5.33 mm    |
| Hardness            | 70 Shore A |
| ID (inner diameter) | 146.05 mm  |
| Temperature Max     | 135 °C     |
| Temperature Min     | -30 °C     |