



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 123.44x1.78 - NBR - Nitrile - 70 Shore A - Black - ORS1848

<https://www.o-ring-stocks.eu/o-ring-123.44x1.78-nbr-nitrile-70-shore-a-black-ors1848>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 1848                     |
| EAN           | 6150549165167            |
| Merk          | Eurolast                 |
| Categorie     | NBR O-Rings - 70 Shore A |
| Materiaal     | Nitrile NBR-Buna         |
| Kleur         | Zwart                    |
| Color         | Black                    |

### Core Spec's

|                   |                                                                          |
|-------------------|--------------------------------------------------------------------------|
| Approval          | None                                                                     |
| Alternative names | Nitrile Rubber - NBR                                                     |
| Chemical Name     | Acrylonitrile butadiene rubber                                           |
| Description 2     | O-ring NBR - Nitrile 123.44x1.78                                         |
| Material          | NBR - Nitrile                                                            |
| Packaging Unit    | O-ring                                                                   |
| Product name      | O-ring 123.44x1.78 Nitrile NBR                                           |
| Size in text      | one hundred and twenty three comma forty four by one comma seventy eight |
| Trade names       | Lanxess - Zeon - and LG Chem                                             |

### Alternative Size

|                     |               |
|---------------------|---------------|
| BS 1806 Size Chart  | BS 546        |
| DIN 3771 Size Chart | 123.44x1.78   |
| SMS 1586 Size chart | 123.44 X 1.78 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 1.78 mm    |
| Hardness            | 70 Shore A |
| ID (inner diameter) | 123.44 mm  |
| Temperature Max     | 135 °C     |
| Temperature Min     | -30 °C     |