



O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 126.67x2.62 - FKM - FPM - Viton - 75 Shore A - Brown - ORS131529

<https://www.o-ring-stocks.eu/o-ring-126.67x2.62-fkm-fpm-viton-75-shore-a-brown-ors131529>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 131529                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 75 Shore A - Brown |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | BRUIN                            |
| Color         | Brown                            |

### Core Spec's

|          |      |
|----------|------|
| Approval | None |
|----------|------|

|                   |                                                                     |
|-------------------|---------------------------------------------------------------------|
| Alternative names | Viton® - FKM                                                        |
| Chemical Name     | Fluorocarbon Rubber                                                 |
| Description 2     | O-ring FKM - FPM - Viton 126.67x2.62                                |
| Material          | FKM - FPM - Viton                                                   |
| Packaging Unit    | O-ring                                                              |
| Product name      | O-ring 126.67x2.62 FKM - FPM - Viton                                |
| Size in text      | one hundred and twenty six comma sixty seven by two comma sixty two |
| Trade names       | Viton® - Du Pont - 3M - Solvay - Daikin                             |

### Alternative Size

|                     |             |
|---------------------|-------------|
| AS568 Size Chart    | AS 159      |
| DIN 3771 Size Chart | 126.67x2.62 |
| ISO 3601 Size Chart | 126.67x2.62 |
| SMS 1586 Size chart | 126.67x2.62 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 2.62 mm    |
| Hardness            | 75 Shore A |
| ID (inner diameter) | 126.67 mm  |
| Temperature Max     | 205 °C     |
| Temperature Min     | -20 °C     |