



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 50.58x2.6 - FKM - FPM - Viton - 70 Shore A - Black - ORS157482

<https://www.o-ring-stocks.eu/o-ring-50.58x2.6-fkm-fpm-viton-70-shore-a-black-ors157482>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 157482                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 70 Shore A - Black |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | ZWART                            |
| Color         | Black                            |

### Core Spec's

|          |      |
|----------|------|
| Approval | None |
|----------|------|

|                   |                                            |
|-------------------|--------------------------------------------|
| Alternative names | Viton® - FKM                               |
| Chemical Name     | Fluorocarbon Rubber                        |
| Description 2     | O-ring FKM - FPM - Viton 50.58x2.6         |
| Material          | FKM - FPM - Viton                          |
| Packaging Unit    | O-ring                                     |
| Product name      | O-ring 50.58x2.6 FKM - FPM - Viton         |
| Size in text      | fifty comma fifty eight by two comma sixty |
| Trade names       | Viton® - Du Pont - 3M - Solvay - Daikin    |

### Alternative Size

|                     |           |
|---------------------|-----------|
| DIN 3771 Size Chart | 50.58x2.6 |
| ISO 3601 Size Chart | 50.58x2.6 |
| SMS 1586 Size chart | 50.58x2.6 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 2.6 mm     |
| Hardness            | 70 Shore A |
| ID (inner diameter) | 50.58 mm   |
| Temperature Max     | 205 °C     |
| Temperature Min     | -20 °C     |