



O-ring-Stocks.eu - Techniparts

Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 633.48x6.99 - FFKM - FFPM - 90 Shore A - Black - ORS99775

<https://www.o-ring-stocks.eu/o-ring-633.48x6.99-ffkm-ffpm-90-shore-a-black-ors99775>

### Specificaties

Productnummer	99775
Merk	Eurolast
Categorie	FFKM O-Rings - 90 Shore A - F909Z93
Materiaal	FFKM - FFPM
Kleur	Zwart
<b>Core Spec's</b>	
Approval	None
Color	Black

Description 2	O-ring FFKM - FFPM 633.48x6.99
Dimensions	633.48x6.99
Equal to	Not Known
Material	FFKM - FFPM
Seal type	O-ring

### Alternative Size

AS568 Size Chart	AS 474
DIN 3771 Size Chart	633.48x6.99
Size in text	six hundred and thirty three comma forty eight by six comma ninety nine
SMS 1586 Size chart	633.48 X 6.99

### Core Spec's

CS (Cross Section)	6.99 mm
Hardness	90 Shore A
ID (Inner diameter)	633.48 mm
Temperature Max	270 °C
Temperature Min	-20 °C

### Technical Spec's

Compression Set	19 %
-----------------	------

### Engels: Technical Specifications

Specific Gravity	1,98 (+/- 0,04) g/cm3
------------------	-----------------------

### Equivalent to

**Specificaties**

Dupont Kalrez® Equivalent	Not Known
Freudenberg Simriz® Equivalent	Not Known
Greene Tweed Chemraz® Equivalent	Not Known
Parker Parafluor® Equivalent	Not Known
Precision Polymer Engineering Perlast® Equivalent	Not Known
Trelleborg Isolast® Equivalent	Not Known

**Other Specs**

Alternative names	FFPM – Dupont Kalrez
Chemical Name	Perfluoroelastomer
Product name	O-ring 633.48x6.99 FFKM - FFPM
Trade names	Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax

**Technical Specifications**

Tensile Strength	18,5 MPa
Ultimate Elongation	110 %