



O-ring-Stocks.eu - Techniparts

Rondweg 26
8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 120x3,53 - FFKM - FFPM - Conform FDA - High Temp - 80 Shore A -

<https://www.o-ring-stocks.eu/o-ring-120x3.53-ffkm-ffpm-high-temp-fda-ec19352004-usp-class-vi-80-shore-a-white-ors188716>

Specificaties

Productnummer	188716
Merk	Eurolast
Categorie	FFKM O-Rings - 80 Shore A - F808W95
Materiaal	FFKM - FFPM
Kleur	WIT
Core Spec's	
Approval	Conform FDA - (300°C)
Color	White

Description 2	O-ring FFKM - FFPM 120x3.53
Dimensions	120x3.53
Equal to	PPE Perlast G80H
Material	FFKM - FFPM
Seal type	O-ring

Alternative Size

AS568 Size Chart	AS 351
DIN 3771 Size Chart	120x3.53
ISO 3601 Size Chart	120x3.53
Size in text	one hundred and twenty zero by three comma fifty three
SMS 1586 Size chart	120 X 3,53

Core Spec's

CS (Cross Section)	3.53 mm
Hardness	80 Shore A
ID (Inner diameter)	120 mm
Temperature Max	300 °C
Temperature Min	-15 °C

Technical Spec's

Compression Set	28 %
-----------------	------

Engels: Technical Specifications

Specific Gravity	2,55 (+/- 0,03) g/cm3
------------------	-----------------------

Equivalent to

Specificaties

Dupont Kalrez® Equivalent Not Known

Freudenberg Simriz® Equivalent Not Known

Greene Tweed Chemraz® Equivalent Not Known

Parker Parafluor® Equivalent Not Known

Precision Polymer Engineering Perlast® Equivalent PPE Perlast G80H

Trelleborg Isolast® Equivalent Not Known

Other Specs

Alternative names FFPM – Dupont Kalrez

Chemical Name Perfluoroelastomer

Product name O-ring 120x3.53 FFKM - FFPM

Trade names Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax

Technical Specifications

Tensile Strength 13,2 MPa

Ultimate Elongation 100 %