



O-ring-Stocks.eu - Techniparts

Rondweg 26
8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 407.8x8.6 - FFKM - FFPM - High Temp - 75 Shore A - Black - Kalrez®

<https://www.o-ring-stocks.eu/o-ring-407.8x8.6-ffkm-ffpm-high-temp-75-shore-a-black-kalrez-4079-ors82366-equivilent>

Specificaties

Productnummer	82366
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F758Z96
Materiaal	FFKM - FFPM
Kleur	Zwart

Basic Specifications

Approval	General Purpose (+330°C)
Color	Black

Alternative names	FFPM – Dupont Kalrez
Equal to	Dupont Kalrez 4079, Freudenberg Simriz 498, Greene Tweed Chemraz 615, PPE Perlast G75B, Trelleborg Isolast J8325 & Isolast J9876,
Material	FFKM - FFPM
Product name	O-ring 23.4x3.53 FFKM - FFPM
Seal type	O-ring

Alternative Size

DIN 3771 Size Chart	407.8x8.6
Size in text	four hundred and seven comma eighty by eight comma sixty
SMS 1586 Size chart	407.8 X 8.6

Basic Specifications

CS (Cross Section)	8.6 mm
Hardness	75 Shore A
ID (Inner diameter)	407.8 mm

Equivalent to

Dupont Kalrez® Equivalent	Dupont Kalrez 4079
Freudenberg Simriz® Equivalent	Freudenberg Simriz 498
Greene Tweed Chemraz® Equivalent	Greene Tweed Chemraz 615
Parker Parafluor® Equivalent	Not Known
Precision Polymer Engineering Perlast® Equivalent	PPE Perlast G75B
Trelleborg Isolast® Equivalent	Trelleborg Isolast J8325 & Isolast J9876

Specificaties

Export Specifications

Country of Origin	IT
Customs Code	40169300

Other Specifications

Chemical Name	Perfluoroelastomer
Description 2	O-ring FFKM - FFPM 407.8x8.6
Trade names	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®

Technical Specifications

Compression Set	19,5 %
Specific Gravity	1,98 (+/- 0.03) g/cm ³
Temperature Max	330 °C
Temperature Min	-15 °C
Tensile Strength	17,8 MPa
Ultimate Elongation	152 %