



O-ring-Stocks.eu - Techniparts

Rondweg 26
8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 29.2x2.4 - FFKM - FFPM - High Temp - 75 Shore A - Black - Kalrez®

<https://www.o-ring-stocks.eu/o-ring-29.2x2.4-ffkm-ffpm-high-temp-75-shore-a-black-kalrez-4079-ors79049-equivilent>

Specificaties

Productnummer	79049
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F758Z96
Materiaal	FFKM - FFPM
Kleur	Zwart
Core Spec's	
Approval	None
Color	Black

Description 2	O-ring FFKM - FFPM 29.2x2.4
Equal to	Dupont Kalrez 4079, Freudenberg Simriz 498, Greene Tweed Chemraz 615, PPE Perlast G75B, Trelleborg Isolast J8325 & Isolast J9876,
Material	FFKM - FFPM
Seal type	O-ring

Alternative Size

DIN 3771 Size Chart	29.2 x 2.4
JIS B 2401 Size Chart	JIS G115
Size in text	twenty nine comma twenty by two comma forty
SMS 1586 Size chart	29.2x2.4

Core Spec's

CS (Cross Section)	2.4 mm
Hardness	75 Shore A
ID (Inner diameter)	29.2 mm
Temperature Max	270 °C
Temperature Min	-20 °C

Technical Spec's

Compression Set	19,5 %
-----------------	--------

Engels: Technical Specifications

Specific Gravity	1,98 (+/- 0.03) g/cm3
------------------	-----------------------

Equivalent to

Specificaties

Dupont Kalrez® Equivalent	Dupont Kalrez 4079
Freudenberg Simriz® Equivalent	Freudenberg Simriz 498
Greene Tweed Chemraz® Equivalent	Greene Tweed Chemraz 615
Parker Parafluor® Equivalent	Not Known
Precision Polymer Engineering Perlast® Equivalent	PPE Perlast G75B
Trelleborg Isolast® Equivalent	Trellebrog Isolast J8325 & Isolast J9876

Other Specs

Alternative names	FFPM – Dupont Kalrez
Chemical Name	Perfluoroelastomer
Product name	O-ring 28x3.5 FFKM - FFPM
Trade names	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®

Technical Specifications

Tensile Strength	17,8 MPa
Ultimate Elongation	152 %