



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 101.2x3.53 - FKM - FPM - Viton - AED - Pressure - Low Temp - 90

<https://www.o-ring-stocks.eu/o-ring-101.2x3.53-fkm-fpm-viton-aed-pressure-low-temp-90-shore-a-black-ors67283>

### Specificaties

|               |                                    |
|---------------|------------------------------------|
| Productnummer | 67283                              |
| Merk          | Eurolast                           |
| Categorie     | FKM O-Rings - 90 Shore A - PLT/AED |
| Materiaal     | FKM - FPM - Viton                  |
| Kleur         | Zwart                              |
| Color         | Black                              |

### Core Spec's

|          |     |
|----------|-----|
| Approval | AED |
|----------|-----|

|                   |                                                             |
|-------------------|-------------------------------------------------------------|
| Alternative names | Viton® - FKM                                                |
| Chemical Name     | Fluorocarbon Rubber                                         |
| Description 2     | O-ring FKM - FPM - Viton 101.2x3.53                         |
| Material          | FKM - FPM - Viton                                           |
| Packaging Unit    | O-ring                                                      |
| Product name      | O-ring 101.2x3.53 FPM - Viton                               |
| Size in text      | one hundred and one comma twenty by three comma fifty three |
| Trade names       | Viton® - Du Pont - 3M - Solvay - Daikin                     |

### Alternative Size

|                     |              |
|---------------------|--------------|
| DIN 3771 Size Chart | 101.2x3.53   |
| SMS 1586 Size chart | 101.2 X 3.53 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 3.53 mm    |
| Hardness            | 90 Shore A |
| ID (inner diameter) | 101.2 mm   |
| Temperature Max     | 205 °C     |
| Temperature Min     | -20 °C     |