



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 227.97x5.33 - NBR - Nitrile - 80 Shore A - Black - ORS3940

<https://www.o-ring-stocks.eu/o-ring-227.97x5.33-nbr-nitrile-80-shore-a-black-ors3940>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 3940                     |
| Merk          | Eurolast                 |
| Categorie     | NBR O-Rings - 80 Shore A |
| Materiaal     | Nitrile NBR-Buna         |
| Kleur         | Zwart                    |
| Color         | Black                    |

### Core Spec's

|          |      |
|----------|------|
| Approval | None |
|----------|------|

|                   |                                                                            |
|-------------------|----------------------------------------------------------------------------|
| Alternative names | Nitrile Rubber - NBR                                                       |
| Chemical Name     | Acrylonitrile butadiene rubber                                             |
| Description 2     | O-ring NBR - Nitrile 227.97x5.33                                           |
| Material          | NBR - Nitrile                                                              |
| Packaging Unit    | O-ring                                                                     |
| Product name      | O-ring 227.97x5.33 Nitrile NBR                                             |
| Size in text      | two hundred and twenty seven comma ninety seven by five comma thirty three |
| Trade names       | Lanxess - Zeon - and LG Chem                                               |

### Alternative Size

|                     |               |
|---------------------|---------------|
| AS568 Size Chart    | AS 373        |
| DIN 3771 Size Chart | 227.97x5.33   |
| SMS 1586 Size chart | 227.97 X 5.33 |

### Core Spec's

|                     |            |
|---------------------|------------|
| CS (Cross Section)  | 5.33 mm    |
| Hardness            | 80 Shore A |
| ID (inner diameter) | 227.97 mm  |
| Temperature Max     | 135 °C     |
| Temperature Min     | -30 °C     |