

**O-ring-Stocks.eu - Techniparts**
Rondweg 26
8091XB, Wezep

**E-MAIL** info@o-ring-stocks.eu
**TEL** +31382024043
**KVK** 08174024

# O-ring 411.48x5.33 - FFKM - FFPM - 75 Shore A - Black - Kalrez® 6375 -

https://www.o-ring-stocks.eu/o-ring-411.48x5.33-ffkm-ffpm-75-shore-a-black-kalrez-6375-ors65198-equivilent

| Specificaties | |
|---|---|
| Productnummer | 65198 |
| sku | 538180 |
| Merk | Eurolast |
| Categorie | FFKM O-Rings - 75 Shore A - F758Z94 |
| Materiaal | FFKM - FFPM |
| Kleur | Zwart |
| Color | Black |
| **Core Spec's** | |
| Approval | General Purpose (+270?C) |
| | |
| Alternative names | FFPM – Dupont Kalrez |
| Chemical Name | Perfluoroelastomer |
| Description 2 | O-ring FFKM - FFPM 411.48x5.33 |
| Material | FFKM - FFPM |
| Packaging Unit | O-ring |
| Product name | O-ring 411.48x5.33 FFKM |
| Size in text | four hundred and eleven comma forty eight by five comma thirty three |
| Trade names | Evolast® - Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax |
| **Alternative Size** | |
| DIN 3771 Size Chart | 411.48x5.33 |
| SMS 1586 Size chart | 411.48 X 5.33 |
| **Core Spec's** | |
| CS (Cross Section) | 5.33 mm |
| Hardness | 75 Shore A |
| ID (inner diameter) | 411.48 mm |
| Temperature Max | 270 ºC |
| Temperature Min | -20 ºC |